

A survey by D.B. Hasbrook on April 3,1850 indicates no stone but the following witnesses: 12" white oak bearing south 84.25 degrees, thence east 74 links, and a 12" hickory bearing south 24.50 degrees, thence west 35 links. (Warren Legal Book P. 24) A survey by H. Blount on March 8,1910 indicates no stones or witnesses. (Warren Legal Book p. 47) Corner referenced by MCS at an unknown date and called a r.r. Spike. Corner referenced by MCS in 1950 and called a stone. Corner referenced by Monroe on 3/13/61 and called a r. r. spike. Corner referenced by Wilcoxen on 10/6/75 and called a r. r. spike. Corner referenced by Jacobs on 10/20/88 and called a r. r. spike. Corner referenced by Kiste on 12/9/94 and called a r.r. Spike. Corner referenced by Wilcoxen on 4/23/2000 and called a p. k. nail. Corner excavated on 10/21/03 and a p.k. Nail was found 2" down. A r. r. spike was found 4" down. A stone with guard stake was found 17" down. A #205 cast iron Harrison Monument was set in position of the stone.

15042205		
REF.	DISTANCE	DESCRIPTION
1.	145.97!	Mag nail w/brass washer E PwP#127-644 A 12"up
2.	28.31'	Railroad spike E PwP#128-644 12"up
3.	85.50'	Road nail N PwP#285-614 12"up
4.	132.35'	Mag nail w/large washer E PwP#89-614 B 18"up